

HASHIMA®

HANDY TYPE NEEDLE DETECTOR

MODEL: **HN-30**

**LIGHT AND EASY
OPERATION**

**MAXIMUM
SENSITIVITY
φ0.8mm**



FEATURES

- **φ0.8 mm steel is detected**
This new handy type needle detector can detect φ0.8 mm steel at 5mm height from detecting unit surface.
- **Battery save function**
Under stand by, Battery mode is changed to save mode automatically and save battery consumption. When take it in hand, the machine starts automatically. New designed detecting circuit is low electric consumption.
- **Light weight**
The weight is only 190g that is more light 10% than previous model. New designed body help you to grip for long time without fatigue.
- **Large size LED lamp**
It is easy to check the detecting result by adapting large size LED lamp.
- **Sensitivity select switch**
The new handy type needle detector adopts Hi/Low sensitivity select switch.

SPECIFICATIONS

Model	HN-30
Detecting Method	Magnetic induction
Detecting ability	Hi : φ0.8mm steel at 5mm height from detecting surface. Low : φ1.0mm steel at 5mm height from detecting surface.
Detecting adjustment	2 step
Detecting area	25mm(W) x 50mm(D)
Alarm method	Buzzer, LED lamp
Power supply	1.5V dry cell battery×2 (AAA)
Dimension	58 (W) × 105 (L) × 50 (H) mm
Weight	212g

Detected material should be used UNTIL METAL ITEM.
※The specification is under standard test condition. The sensitivity depends on the working condition.
We have no responsibility that needle chip, iron chip, etc. come out after detecting under non-standard condition.

 **HASHIMA CO., LTD.**

BUSINESS OFFICE : 7-6, RYOGU Gifu-CITY, JAPAN

TEL 81-58-247-8400, 81-58-245-4501 FAX 81-58-240-5775

SINGAPORE OFFICE : TEL 65-2858131 FAX 65-2858132

HASHIMA AMERICA : TEL : 1-805-277-0618 FAX : 1-805-277-1864

KUNSHAN(CHINA) OFFICE TEL : 86-512-57771838 FAX : 86-512-57771848

URL <http://www.hashima.co.jp>